


Slimline RSR



Advantages

- Lightweight, compact ducted filter module for clean processes or medical suites
- Low pressure drop saves energy and low life-cycle cost reduces disposal cost

Description: Low-profile ducted filter module for HEPA/ULPA filters.

Typical applications: Pharmaceutical and semiconductor manufacturing facilities, medical facilities and other clean process applications.

Efficiency: 95% at 0.3 μ to 99.9995% at Most Penetrating Particle Size (MPPS).

Media: Microfine glass media, with continuous glass filament separators formed into a single mini-pleat filter pack.

Temperature: Maximum continuous operating temperature of 200° F (93° C).

Ratings: Tested in accordance with IEST Recommended Practice for Testing HEPA Filters. UL 900.

Consult Literature 3422 for detailed information.

Model	Dimensions (inches, W x L x H)	Collar Diameter (inches)	Shipping Weight (lbs)
1.50" T-Bar			
SL RSR 23.62-23.62-10	23.62 X 23.62 X 5.3	10	34
SL RSR 23.62-23.62-12	23.62 X 23.62 X 5.3	12	34
SL RSR 23.62-35.62-10	23.62 X 35.62 X 5.3	10	40
SL RSR 23.62-35.62-12	23.62 X 35.62 X 5.37	12	40
SL RSR 23.62-41.62-10	23.62 X 41.62 X 5.3	10	46
SL RSR 23.62-41.62-12	23.62 X 41.62 X 5.3	12	46
SL RSR 23.62-47.62-10	23.62 x 47.62 x 5.37	10	50
SL RSR 23.62-47.62-12	23.62 x 47.62 x 5.37	12	50
2.0" T-Bar			
SL RSR 23.12-23.12-10	23.62 X 23.62 X 5.3	10	34
SL RSR 23.12-23.12-12	23.62 X 23.62 X 5.3	12	34
SL RSR 23.12-35.12-10	23.62 X 35.62 X 5.3	10	40
SL RSR 23.12-35.12-1	23.62 X 35.62 X 5.37	12	40
SL RSR 23.12-41.12-10	23.62 X 41.62 X 5.3	10	46
SL RSR 23.12-41.12-12	23.62 X 41.62 X 5.3	12	46
SL RSR 23.12-47.12-10	23.62 x 47.62 x 5.37	10	50
SL RSR 23.12-47.12-12	23.62 x 47.62 x 5.37	12	50