

## Filters

**Ultra-Pac® Absolute®****Advantages**

- Ideal for use in existing systems that require increased airflow
- Close-pleat technology increases filter media area providing a lower resistance to airflow resulting in energy savings

**Description:** MERV 16 or HEPA grade filter in a 16-gauge galvannealed steel enclosing frame.

**Typical applications:** Built-up filter banks, rooftops, and air handlers in medical facilities, pharmaceuticals, and clean process manufacturing.

**Efficiency:** MERV 16 or 99.99% at 0.3μ.

**Media:** 7-inch deep mini-pleated microfine glass media pack in a nominal 12" deep enclosure, sealed with fire-retardent polyurethane sealant.

**Recommended final pressure drop:** Rule of thumb: change filter when the initial pressure drop doubles, or consult factory.

**Temperature:** Maximum continuous operating temperature of 160° F (70° C).

**Ratings:** Tested in accordance with IEST Recommended Practice for Testing HEPA Filter.

See Literature 1824 for more details.

Model Number	Efficiency @ 0.3 Micron	Nominal Size (inches)	Airflow Capacity (cfm)	Resistance @ Capacity (inches w.g.)	Media Area (sq. ft.)	Shipping Weight (lbs.)
GGEM-200-**	95%	12 x 12 x 11.50	240	0.50	38	10
GGEM-450-**	95%	12 x 24 x 11.50	520	0.50	77	17
GGEM-725-**	95%	18 x 24 x 11.50	820	0.50	116	24
GGEM-1000-**	95%	24 x 24 x 11.50	1120	0.50	155	32
GGEM-1250-**	95%	30 x 24 x 11.50	1410	0.50	194	40
TREM-200-**	95%	12 x 12 x 11.50	300	0.50	57	12
TREM-450-**	95%	12 x 24 x 11.50	650	0.50	116	20
TREM-725-**	95%	18 x 24 x 11.50	1020	0.50	174	28
TREM-1000-**	95%	24 x 24 x 11.50	1400	0.50	233	34
TREM-1250-**	95%	30 x 24 x 11.50	1770	0.50	290	43
GGEA-200-**	99.99%	12 x 12 x 11.50	225	1.0	41	10
GGEA-450-**	99.99%	12 x 24 x 11.50	475	1.0	78	17
GGEA-725-**	99.99%	18 x 24 x 11.50	750	1.0	126	24
GGEA-1000-**	99.99%	24 x 24 x 11.50	1040	1.0	169	32
GGEA-1250-**	99.99%	30 x 24 x 11.50	1300	1.0	211	40
TREA-200-**	99.99%	12 x 12 x 11.50	340	1.0	61	12
TREA-450-**	99.99%	12 x 24 x 11.50	725	1.0	126	20
TREA-725-**	99.99%	18 x 24 x 11.50	1140	1.0	188	28
TREA-1000-**	99.99%	24 x 24 x 11.50	1560	1.0	253	34
TREA-1250-**	99.99%	30 x 24 x 11.50	1970	1.0	315	43

Replace \*\* in model number with None for no downstream gasket, 01 for downstream gasket, 10 for upstream gasket, or 11 for gaskets upstream and downstream.